

## Regulator de temperatura

## Temperature Control Unit

### S5221/ 1 (WTD-35/M)

Circuite: 1  
Conectarea: Schuko/5-pin/4-pin  
Termocupluri: Fe-CuNi, Ni-CrNi, PT100

Control circuit: 1  
Connection: Schuko/5-pol/4-pol  
Thermocouples: Fe-CuNi, Ni-CrNi, PT100

- Afisaj dublu cu 4 cifre pentru setarea valorii actuale
- Functionare Soft-Start
- Comutare manuala/automata
- Selectabil 2 puncte de referinta (Stand-by)
- Auto-optimizare inteligenta
- Contactor pentru semnal de alarma, operat de releu
- Blocare tastatura
- Carcasa metalica

- Two 4-digits displays for set actual values
- Soft-start-function
- Manual / automatic switchable
- Two set-points selectable (Stand-by)
- Smart selfoptimisation
- Relay-operated contactor alarm signal
- Keyboard interlocking
- Metal case

Nr. / No.
S5221/ 1



Nr. / No.	S5221/ 1	
Tensiune Voltage	V-AC	230
Frecventa Frequency	Hz	50 - 60
Puterea Wattage	W	3.300
Dimensiuni Dimension	mm	220 x 100 x 290 (L x l x A) (W x H x D)

