

**Conectori cablu GS
(pentru UFT)****Tip/Type GS 25**

- Carcasa din aluminiu turnat
- Insertie ceramica
- Constructie dreapta
- 2 - pini cu contact la pamant
- 25A / 400V

- Die-cast aluminium housing
- Ceramic insert
- Straight construction
- 2-pole with earth contact
- 25A / 400V

**Tip/Type GS 20**

- Carcasa din aluminiu turnat
- Insertie ceramica
- Constructie la 90 de grade
- 2 - pini cu contact la pamant
- 25A / 400V

- Die-cast aluminium housing
- Ceramic insert
- Construction: angled, 90°
- 2-pole with earth contact
- 25A / 400V

**Conectori cablu GS,
Carcasa cauciuc rezistent****Tip/Type GS 25 VG**

- Carcasa cauciuc rezistent
- Constructie dreapta
- 2 - pini cu contact la pamant
- 10/16A / 250V
(25A on request)

- Solid-rubber plug housing
- Straight construction
- 2-pole socket with earth contact
- 10/16A / 250V
(25A on request)

temperatura max.: 200°C,
temperatura pe termen scurt: 300°C

max. temperature: 200°C,
short-term temperature: 300°C

**Tip/Type GS 20 VG**

- Carcasa cauciuc rezistent
- Constructie la 90 de grade
- 2 - pini cu contact la pamant
- 10/16A / 250V
(25A la cerere)

- Solid-rubber plug housing
- Construction: angled, 90°
- 2-pole socket with earth contact
- 10/16A / 250V
(25A on request)

temperatura max.: 200°C,
temperatura pe termen scurt: 300°C

max. temperature: 200°C,
short-term temperature: 300°C

