

Releu static

Solid State Relay

S5201/ 1

Nr. / No.
S5201/ 1



Nr. / No.	S5201/ 1	
Funcțiune Function	Monofazica, comutare pe zero 1-Phaes Zero Switching	
Montaj Mounting	Montare pe panou Panel mounting	
Dimensiuni Dimension	mm	58,2 x 44,8 x 26,8 (L x l x A) (W x H x D)
Interval Range	A AC _{eff}	25
Alimentarea Supply	VAC _{eff}	480
Conectarea Connection	Terminal surub Screw Terminal	
I/I Semnal I/O Signal	VDC	4,5 - 32
Tip Type	LED si Varistor, capac de protectie LED and Varistor, protection cover	

Statie de putere

Power-Stage

S5202/ 1 (LT-20)

Nr. / No.
S5202/ 1



Nr. / No.	S5202/ 1	
Funcțiune Function	Monofazica, comutare pe zero 1-Phaes Zero Switching	
Montaj Mounting	DIN Montare pe sina DIN-rail	
Dimensiuni Dimension	mm	22,5 x 103 x 80,5 (L x l x A) (W x H x D)
Interval Range	A Acrms	20
Alimentarea Supply	VAC	42 - 660
Conectarea Connection	Terminal surub Screw Terminal	
I/I Semnal I/O Signal	VDC	4 - 32
Model Model	Radiator incorporat Integrated heatsink	